



Acouline Care & Maintenance Guide

Keeping Your Acouline Products Looking Their Best

Acouline acoustic panels are designed for long-lasting performance with minimal maintenance. Regular vacuuming using a soft brush attachment will help prevent dust build-up. Most marks can be removed using a mild detergent solution, followed by rinsing with clean water and blotting dry. Always test any cleaning method on an inconspicuous area first. Spot clean only and avoid abrasive cleaning methods.

Disinfecting

Acouline panels may be disinfected using 70% isopropyl alcohol, 70% ethanol, or suitable quaternary ammonium disinfectants. Apply with a soft cloth rather than spraying directly onto the panel.

General Care

- Vacuum regularly
- Spot clean only
- Avoid stiff brushes and abrasive pads
- Blot spills immediately
- Allow panels to air dry naturally
- Avoid solvent-based cleaners and steam cleaning.

Common Stain Treatment

Stain	Treatment
Blood	A,C
Chewing Gum	B,C,D,H
Coffee/Tea/Juice	A,C
Grease/Oil	B,C,D
Mud	B,C
Wine	A, Add Salt, C
Paint (Water)	A,C,E
Paint (Oil)	A,C,D,G

Treatment Key

- A** Blot excess immediately.
- B** Remove excess with a plastic scraper.
- C** Clean using mild carpet/upholstery shampoo, rinse and blot dry.
- D** Apply dry-cleaning solvent sparingly.
- E** Soften with glycerine or petroleum jelly.
- F** Use non-greasy nail polish remover.
- G** Treat with mineral turpentine.
- H** Freeze then remove chewing gum.
- I** Use extraction cleaner if appropriate.
- J** Replace damaged section if required.



Disclaimer

This guide provides general maintenance recommendations for Acouline acoustic products. Cleaning results may vary depending on the stain and cleaning method used. Always follow cleaning product instructions and test in an inconspicuous area before full application. Furnx accepts no responsibility or liability for any loss or damage that may arise from the implementation of the treatments listed above